



B 201 RH



www.ausa.com

AUSA Center, S.L.U. ● Ctra. de Vic, Km 2.8 - P.O.B. 194, 08243 Manresa - BARCELONA (ESPAÑA) Tel.: +34 93 874 73 11 E-mail:

ISO 9001

ISO 14001



(Sede central AUSA-Manresa)

- AUSA Madrid** ● Pol. Ind. Coslada-Marconi 15-17, 28823 Coslada - MADRID (ESPAÑA) Tel.: +34 91 669 00 06 E-mail: ausa.madrid@ausa.com
- AUSA France** ● Z. I. Saint Charles-Rue de Zürich, 66000 PERPIGNAN (FRANCE) Tel.: +33 (0) 4 68 54 38 97 E-mail: ausa.france@ausa.com
- AUSA** ● Unit 16 Hollows Works - Shawlough Road - Rochdale - Lancs OL12 6LN (U.K.) Tel.: +44 (0) 1706 64 96 91 E-mail: ausa.uk@ausa.com
- AUSA Repräsentanzbüro Deutschland** ● Heinrich-Welken Straße 5, 59069 HAMM - RHYERN (GERMANY) Tel.: +49 2385922245 E-mail: ausa.deutschland@ausa.com
- AUSA Northamerica Corp.** ● 2655 Le Jeune Road - Suite 808, CORAL GABLES FL 33134 (USA) Toll free: 1 800 820 AUSA E-mail: ausa.corp@ausa.com
- BEIJING Rep. office** ● Address Room 527, HengXiang Building, Tuanjiehu Nanli, Chaoyang District. - Beijing 100026 CHINA Tel: 86-10-8597 1983 - Fax: 86-10-8597 1993 - E-mail: ausa.china@ausa.com



B 201 RH



SPECIFICATIONS

B 201 RH

Hopper capacity	(l)	1250
Sweeper attachment capacity	(l)	245
Elevation and unloading of the sweeper attachment		Hydraulic
Hopper unloading height	(mm)	1195
Engine	Diesel	KUBOTA V1505
	Power s/DIN 6270B (KW/CV)	23.55 / 32.2 (2600 rpm)
	Power s/DIN 70020 (KW/CV)	25.6 / 34.8 (2600 rpm)
	Nº cylinders	4
	Coolant	Water
Traction		4 x 4 permanent Compen® System
Transmission		2-speed hydrostatic Electric gear inverter on the joystick
Ignition		Electric
Speed (maximum)	(Km/h)	20
Sweep width	(mm)	2370
Recomended sweep speed	(Km/h)	4
Central brush width	(mm)	1200
Central brush diameter	(mm)	450
Side brush diameter	(mm)	800
Unloaded weight (with full tanks)	(Kg)	2352
Maximum slope	Under full load	42 %
	Sweeping	20 %
Tyres	Front	10,0 / 80-12
	Rear	10,0 / 80-12
Steering		Hydraulic. Working pressure 80 bar
External turning circle	(mm)	4200
Tank capacity	Fuel (l)	40
	Hydraulic oil (l)	40
	Watter supply for sprinkling (l)	450
Water pump		Electric of 12,5 l/min
Total sprinkling width	(mm)	2500
Hand Brake		Sealed oil-immersed
Parking brake		multidisc
Hydraulic circuit		Gear pump of 8 cc Working pressure 190 bar

STANDARD EQUIPMENT

Ergonomic seat
Rotating beacon
Acoustic reverse indicator
Seat belt
Anti vandal security system
ROPS Protective roof
Self-loading bucket of 180 l., easily interchangeable for the sweeper kit, wich allows to perform as a dumper.

OPTIONAL EQUIPMENT

Lighting equipment
FOPS/ROPS Protective roof
Shovel teeth
Second seat

MKT23007_00-03/2008

AUSA reserves the right to make any changes in the specifications without prior notice. Machines in photos may include some optional equipment.